

# 3" Submersible Pump

Type 3TP

#### **APPLICATIONS**

- Domestic water supply systems (manufactured accordingly to TIFQ, ACS, WRAS and all the European certification for domestic drinking water)
- Small waterworks
- Irrigation and water pumping in general
- · Water transfering
- Pressure boosting of clear water for agriculture, domestic or industrial use
- Adapting old unusable 4" water wells

#### **FEATURES**


- Plug & Play friendly usage
- Single-phase 230V input (power source)
- · Easy to handle and install
- Compact and robust construction
- High efficiency pump and motor
- Energy saving
- Plug in type motor cable : available with 15, 30, 45 and 60 m length
- · Additional controls may be installed
- Soft start
- Fully protected :
  - Over temperature protection
  - Dry-running protection
  - Over load protection
  - High/low voltage protection
  - Phase failure protection
  - Surge voltage protection





#### **PERFORMANCE CHART**

(according to ISO 9906 Attachment A)



### **PERFORMANCE TABLE**

Model	Stage	Connection	Motor power	Capacity	Head	Dimension [mm]	
		size	[kW]	[m³/h]	[m]	Without PFC	With PFC
3TP2	4	Rp 1"	0.6	3.3	57.6	894	918
	6	Rp 1"	0.9	3.3	81	973	997
	9	Rp 1"	1.5	3.3	128	-	1200
3TP3	3	Rp 1"	0.6	4.5	48	870	894
	5	Rp 1"	0.9	4.5	77	950	974
	8	Rp 1"	1.5	4.5	127	-	1175
3TP5	4	Rp 1"¼	0.9	7.5	52	946	970
	7	Rp 1"¼	1.5	7.5	90.9	-	1187

### **PUMP SPECIFICATION**

Capacity (best efficiency point)	[m <sup>3</sup> /h]	2 - 3 - 5	
Head	[m]	Max. 147	
Maximum temperature of the liquid	[°C]	35	
Maximum immersion	[m]	150	
Maximum presence of sand	[ppm]	50	
Material	Discharge and suction casing	ASTM CF8 (SCS13)	
THE COLUMN TO TH	Impeller, Interstage casing, Diffuser	PPO mod glass fiber reinforced	
	Shaft	AISI 304	

#### \* Dimensional details are provided for reference only.

## **MOTOR SPECIFICATION**

Туре	Three-phase induction motor built in VFD			
Voltage	[V]	230		
Frequency	[Hz]	50 / 60		
Output	[kW]	0.6 - 0.9 - 1.5		
Rotation speed	[min <sup>-1</sup> ]	8400		

**EBARA Pumps Malaysia Sdn Bhd**6, Jalan TP3, UEP Subang Jaya Industrial Park,
47620 Subang Jaya, Selangor, Malaysia.
Tel: 03-8023 6622 Fax: 03-8023 9355

Email: sales@ebara.com.my Website: www.ebara.com.my



Authorised dealer:

<sup>\*</sup> All specifications are subject to change without prior notice.