



Control Boxes

Type UBX SERIES

TECHNICAL FEATURES

Control Box suitable to drive and protect single phase submersible motors 50 Hz / 60 Hz

- Enclosure made in robust Painted Steel
- Available in PSC - CSCR - CSIR version
- Voltmetric Rely Easy to install - 115 V or 230 V available
- Capacitor Start Available as option
- Made under NEMA 3 R for indoor and outdoor installation
- Easy Access cable terminals up to "AWG 8"
- External Eccess to Thermal Protection
- User Friendly to GND Terminal
- Run Capacitor for better efficiency and silent running
- Start Capacitor for Higher Starting Torque

UBX Range :

CSIR : from 0.5 Hp 1 Hp

PSC : from 0.5 Hp to 3 Hp

CSCR : from 0.5 Hp to 3 Hp





Codice	kW	Hp	Volts	Crun μF	Capacitor V	Max running amps A	C Start μF	Capacitor start V V
20201000	0.37	0.50	115			13	250-300	280
20201010	0.37	0.50	230			6.4	250-300	280
20201020	0.55	0.75	230			9.4	86-103	280
20201040	0.75	1.00	230			10.6	105-126	280
20201060	1.10	1.50	230	10	450	11.8	105-126	280
20201080	1.50	2.00	230	20	450	13.6	105-126	280
20201100	2.20	3.00	230	35	450	17.2	208-250	280
20201120	3.70	5.00	230	80	450	28	250-280	280

* Dimensional details are provided for reference only.

* All specifications are subject to change without prior notice.



EBARA Pumps Malaysia Sdn Bhd
 6, Jalan TP3, UEP Subang Jaya Industrial Park,
 47620 Subang Jaya, Selangor, Malaysia.
 Tel : 03-8023 6622 Fax : 03-8023 9355
 Email : sales@ebarapumps.com.my
 Website : www.ebarapumps.com.my



Authorised dealer: